


1.25Gb/s 80km SFP
RTXM182-831 & RTX182-832



RTXM182-831	RTXM182-832	1.25Gb/s	LC	SFP	PIN
			EEPROM	-	.
LC					
3.3V					
1.25Gb/s					
PECL					
80					
			: 0°C ~70°C		
			RoHS		
-					

SFP MSA (INF-8074i)
 IEEE802.3ah
 ITU-T G.957

		Icc	mA	-	-	300	1
			mV	150	-	1100	
			mV	300	-	600	
TX_fault /LOS	(TTL)	VOH	V	2.0	-	Vcc	
		VOL		0	-	0.8	
TX_disable	(TTL)	VOH	V	2.0	-	Vcc	
		VOL		0	-	0.8	
1.25G BIDI SFP							
		Po	dBm	-2		+4	EOL
		λ c	nm	1480	1490	1500	DFB-LD
				1560	1570	1580	DFB-LD
		EX	dB	9			
(20dB)		$\Delta\lambda$	nm	1			
			dB	30			
		Tp-p	ps	267			2
		RIN	dB/Hz	-120			
IEEE802.3ah							
		Poff	dBm	-	-	-45	
		λ c	nm	1560	1580		
				1480	1500		
		S	dBm	-26			
		Pin	dBm	0			
			dB	-26			
				-35			
			dB	0.5	3	5	
			dB	1			

1.25Gbps 23

RTXM182-831	SFP	1.25G	1490nm DFB-LD	-2~+4 dBm	PIN 1570nm	< -26dBm	0~70°C	80km	GE
RTXM182-832	SFP	1.25G	1570nm DFB-LD	-2~+4 dBm	PIN 1490nm	< -26dBm	0~70°C	80km	GE