


Patch Cord for Cat5e/Cat6/Cat7A



Product Introduction

It is used in 10Base-T, 100Base-TX, 1000Base-T and ATM or 1.2Gb/s ATM Ethernet 2.4G network application

Features

- Metallic shield layer, drain wire diameter AWG26-27, high-performance shielding crystal heads.
- RJ45 plugs on both ends, 50μm gold-plated layer at pin leg.
- Compatible with T568A/B terminated line order, various of color (normally deep blue, light blue, yellow, red, gray) and length alternative.
- Outer sheath one-time molding, reduce stress when plug in and plug out, protect crystal head.
- Outer sheath: PVC, LSZH, PE is alternative.
- Patch cords adopt more flexible cord, and can withstand repeated bending.
- Durability: 1000 Times.


Standards

- ISO/IEC 11801 Class D
- ANSI-TIA/EIA 568 C.2 Cat5e or ISO/IEC 11801 Class E
- ANSI-TIA/EIA 568 C.2 Cat6

Specification

- 100%open circuit, short circuit and dislocation test.
- Insulation resistance: direct voltage 300V, insulation resistance: 10MΩ.
- Conductor resistance: 3Ω.
- Compliant with FLUKE CAT.5e/6 testing.

Ordering information



Cable