

× ñ û4ý

GPON OLT f ~AîAÑ+X ¾ s v \$À y5•5 ÄQ ‡ 5 1490nm DFBF 5 Q ? 4 ~¼ 1310nm
0± Q ? APD Ö f j Ä

4 ~G 6 ¯+XQ x 1490nm DFB%ð y ~È +O uLì &1V 8 class-1-l ¹ ~ 7 ö Ä%ð yPî Ø ~ 5

APC İ7- ¼\$Y Ö>• ¯ İ7- È X\$Y Ö93 \$ ¼ / - ~ O µ 1 4 y İ)· ¼# , y" 0c Ê Ä

Ö f jG 6 6 APD Ò#{ ~¼0± Q ? }5ž n W ~Lö @ X 0C§ Äj ¶7- È FO *0û &L\$ ÈD7- ý
K ¯ CID

„ RoHs 1V 8

Ä+X

Optical transceiver for Gigabit-capable Passive Optical Networks (GPON) Class B+OLT

7 ö

z ITU-T G.984.2 Class B+

z Small Form-factor Pluggable (SFP) Transceiver MultiSource Agreement July 5, 2000

(© W

ò	1V'	... }	0 ? I	» I	0 W I
Ɛ+e »	V _{cc}	V	3.135	3.3	3.465
Ɛ\$Y Ö93 \$	T _{op}		0	–	70
Ɛ 'FO)· (41)		Mbps	–	2488.32	–
Ɛ 'FO)· (Ö f1)		Mbps	–	1244.16	–

AÖC] Ÿ

Part No	Specification									Application Code
	Package	TX DataRate	Laser	Optical Power	Detector	RX DataRate	Sensitivity	Temp	Standrad	
RTXM167-522	SFP	2.488Gb/s	1490nm DFB	1.5~5dBm	APD	1.244Gb/s	<-28dBm	0~70°C	GPON OLT Class B+	CLASS B+

Ports Definition